

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application.

Listing of Claims:

1. (Currently Amended) A converter comprising:
a chassis comprising:
a plurality of first ports;
a plurality of second ports wherein the second ports are of a different type than the first ports and wherein each first port is electrically coupled to a distinct second port to create a plurality of port pairs; and
a monitor electrically coupled to the plurality of port pairs to monitor information concerning a single, user-selectable port pair, the monitor including a switching mechanism for selecting a port pair to be monitored.
2. (Original) The converter of claim 1 wherein the information monitored by the monitor includes activity on the first and second port of a selected pair.
3. (Previously Presented) The converter of claim 1 wherein the information monitored by the monitor includes whether the first and second port of a selected port pair are properly terminated.
4. (Original) The converter of claim 1 wherein the plurality of first ports are electrical connectors that receive signals from copper wiring and the plurality of second ports are optic connectors that receive signals from fiber optic cables.
5. (Original) The converter of claim 1 wherein the plurality of first ports are electrical connectors that receive signals from twisted pair wiring and the plurality of second ports are optic connectors that receive signals from multimode fiber.

6. (Original) The converter of claim 1 wherein the plurality of first ports are electrical connectors that receive signals from twisted pair wiring and the plurality of second ports are optic connectors that receive signals from single mode fiber.
7. (Original) The converter of claim 1 wherein the plurality of first ports are electrical connectors that receive signals from coaxial cables and the plurality of second ports are optic connectors that receive signals from multimode fiber.
8. (Original) The converter of claim 1 wherein the plurality of first ports are electrical connectors that receive signals from coaxial cables and the plurality of second ports are optic connectors that receive signals from single mode fiber.
9. (Original) The converter of claim 1 wherein the plurality of first ports are optical connectors that receive signals from single mode fiber and the plurality of second ports are optical connectors that receive signals from multimode fiber.
10. (Original) The converter of claim 1 wherein the plurality of first ports are RJ-45 jacks and the plurality of second ports are fiberoptic connectors.
11. (Original) The converter of claim 1 wherein the monitor further comprises a display for displaying the selected port pair being monitored.
12. (Original) The converter of claim 11 wherein the display is a digit display.
13. (Original) The converter of claim 11 wherein the display is a liquid crystal display.
14. (Currently Amended) The converter of claim 1 wherein the switching mechanism ~~monitor further~~ comprises a switch for selecting a port pair to be monitored.
15. (Original) The converter of claim 14 wherein the switch is a toggle switch.

16. (Original) The converter of claim 14 wherein the switch includes a pair of switches.
17. (Original) The converter of claim 16 wherein the pair of switches are momentary switches.
18. (Previously Presented) The converter of claim 1 further comprising a plurality of indicators for indicating activity on the selected port pair being monitored and termination of first and second port of the selected port pair being monitored.
19. (Original) The converter of claim 18 wherein the plurality of indicators are light emitting diodes.
20. (Original) The converter of claim 11 wherein the display flashes if a fault condition exists for the port pair being monitored.
21. (Original) The converter of claim 1 wherein the monitor is detachably coupled to the chassis.
22. (Original) The converter of claim 1 wherein the plurality of first ports are grouped together in a first group and the plurality of second ports are grouped together in a second group that is located away from the first group.
23. (Original) The converter of claim 22 wherein the monitor is located between the first and second group.
24. (Currently Amended) A monitor comprising:
an input for receiving signals from multiple ports wherein the ports include a plurality of first ports of a first type and a plurality of second ports of a second type that are different than the first type wherein the ports are electrically coupled so that a first port is electrically coupled to a distinct second port to form a port pair;

means electrically coupled to the input for ~~allowing~~ switching user-selection of a single port pair to monitor; and

a display electrically coupled to the means for switching user-selection ~~selecting~~ and the input to display the port pair ~~is~~ being monitored.

25. (Previously Presented) The monitor of claim 24 wherein the display also displays whether a fault condition is present for the port pair being monitored.

26. (Currently Amended) The monitor of claim 24 further comprising:
an indicator electrically coupled to the means for switching user-selection ~~selecting~~ wherein the indicator indicates a condition about the port pair being monitored.

27. (Original) The monitor of claim 24 wherein each port pair is assigned a unique number and the display is a light emitting digit display that displays the unique number of the port pair being monitored.

28. (Currently Amended) The monitor of claim 24 wherein the means for switching user-selection ~~selecting~~ is a switch.

29. (Currently Amended) The monitor of claim 24 wherein the means for switching user-selection ~~selecting~~ is a pair of momentary switches.

30. (Currently Amended) The monitor of claim 26 ~~[[24]]~~ wherein the indicator is a light emitting diode.

31. (Original) The monitor of claim 24 wherein the first ports are RJ-45 ports and the second ports are fiber optic ports.

32. (Original) The monitor of claim 24 wherein the plurality of first ports are electrical connectors that receive signals from twisted pair wiring and the plurality of second ports are optic connectors that receive signals from multimode fiber.

33. (Original) The monitor of claim 24 wherein the plurality of first ports are electrical connectors that receive signals from twisted pair wiring and the plurality of second ports are optic connectors that receive signals from single mode fiber.
34. (Original) The monitor of claim 24 wherein the plurality of first ports are electrical connectors that receive signals from coaxial cables and the plurality of second ports are optic connectors that receive signals from multimode fiber.
35. (Original) The monitor of claim 24 wherein the plurality of first ports are electrical connectors that receive signals from coaxial cables and the plurality of second ports are optic connectors that receive signals from single mode fiber.
36. (Original) The monitor of claim 24 wherein the plurality of first ports are optical connectors that receive signals from single mode fiber and the plurality of second ports are optical connectors that receive signals from multimode fiber.
37. (Original) The monitor of claim 24 wherein the display is a digit display.
38. (Original) The monitor of claim 24 wherein the display is a liquid crystal display.
39. (Currently Amended) A monitor circuit board assembly comprising:
an input for receiving signals from a plurality of port pairs of a converter;
a port pair selector for allowing user-selection of which single port pair to monitor,
wherein the port pair selector includes a switching mechanism;
a monitor circuit coupled to the input and port pair selector wherein the monitor circuit monitors at least one condition of the port pair selected; and
a display to indicate which of a plurality of port pairs is being monitored.
40. (Original) The assembly of claim 39 wherein the display also displays a fault condition on the port pair being monitored.

41. (Original) The assembly of claim 39 wherein the display is an LED digit display.
42. (Original) The assembly of claim 39 wherein the display is a liquid crystal display.
43. (Currently Amended) The assembly of claim 39 wherein the switching mechanism port pair selector is a switch.
44. (Currently Amended) The assembly of claim 39 wherein the switching mechanism port pair selector is a pair of switches.
45. (Original) The assembly of claim 44 wherein the pair of switches are momentary switches.
46. (Original) The assembly of claim 39 wherein the plurality of port pairs includes first electrical ports that receive signals from twisted pair wiring and a plurality of second optical ports that receive signals from multimode fiber.
47. (Original) The assembly of claim 39 wherein the plurality of port pairs includes first electrical ports that receive signals from twisted pair writing and a plurality of second optical ports that receive signals from single mode fiber.
48. (Original) The assembly of claim 39 wherein the plurality of port pairs includes first electrical ports that receive signals from coaxial cables and a plurality of second optical ports that receive signals from multimode fiber.
49. (Original) The assembly of claim 39 wherein the plurality of port pairs includes first electrical ports that receive signals from coaxial cables and a plurality of second optical ports that receive signals from single mode fiber.

50. (Original) The assembly of claim 39 wherein the plurality of port pairs includes first optical ports that receive signals from single mode fiber and a plurality of second optical ports that receive signals from multimode fiber.

51. (Currently Amended) A monitor for a converter, the monitor comprising:
an input electrically coupled to a plurality of port pairs wherein each of the port pairs includes a port of a first type electrically coupled to a port of a second type wherein the first type accepts signals in a different format than the second type;
a selector coupled to the input for allowing user-selection of one of the plurality of port pairs to monitor, wherein the selector includes a switching mechanism;
a monitor circuit for monitoring at least one condition of the port pair selected; and
a display coupled to the input for displaying the port pair being monitored and whether a fault condition is present at that port pair being monitored.

52. (Original) The monitor of claim 51 further comprising a plurality of indicators coupled to the input wherein each of the plurality of indicators indicates a particular type of fault condition for the twisted pair being monitored.

53. (Original) The monitor of claim 51 wherein the plurality of first ports are electrical connectors that receive signals from twisted pair wiring and the plurality of second ports are optic connectors that receive signals from multimode fiber.

54. (Original) The monitor of claim 51 wherein the plurality of first ports are electrical connectors that receive signals from twisted pair wiring and the plurality of second ports are optic connectors that receive signals from single mode fiber.

55. (Original) The monitor of claim 51 wherein the plurality of first ports are electrical connectors that receive signals from coaxial cables that the plurality of second ports are optic connectors that receive signals from multimode fiber.

56. (Original) The monitor of claim 51 wherein the plurality of first ports are electrical connectors that receive signals from coaxial cables and the plurality of second ports are optical connectors that receive signals from single mode fiber.
57. (Original) The monitor of claim 51 wherein the plurality of first ports are optical connectors that receive signals from single mode fiber and the plurality of second ports are optical connectors that receive signals from multimode fiber.
58. (Original) The monitor of claim 51 wherein the display is a digit display.
59. (Original) The monitor of claim 51 wherein the display is a liquid crystal display.
60. (Currently Amended) The monitor of claim 51 wherein the switching mechanism ~~selector~~ is a switch.
61. (Currently Amended) The monitor of claim 51 wherein the switching mechanism ~~selector~~ includes a pair of switches.
62. (Original) The monitor of claim 61 wherein the pair of switches are momentary switches.
63. (Previously Presented) A converter comprising:
a chassis comprising:
 a plurality of first ports;
 a plurality of second ports wherein the second ports are of a different type than the first ports and wherein each first port is electrically coupled to a distinct second port to create a plurality of port pairs; and
 a monitor electrically coupled to the plurality of port pairs to monitor information concerning a selected port pair;
 wherein the monitor further comprises a display for displaying the selected port pair being monitored, wherein the display is a liquid crystal display.

64. (Previously Presented) A converter comprising:
a chassis comprising:
a plurality of first ports;
a plurality of second ports wherein the second ports are of a different type than the first ports and wherein each first port is electrically coupled to a distinct second port to create a plurality of port pairs; and
a monitor electrically coupled to the plurality of port pairs to monitor information concerning a selected port pair;
wherein the monitor further comprises a switch for selecting a port pair to be monitored.
65. (Previously Presented) The converter of claim 64 wherein the switch is a toggle switch.
66. (Previously Presented) The converter of claim 64 wherein the switch includes a pair of switches.
67. (Previously Presented) The converter of claim 66 wherein the pair of switches are momentary switches.
68. (Previously Presented) A monitor comprising:
an input for receiving signals from multiple ports wherein the ports include a plurality of first ports of a first type and a plurality of second ports of a second type that are different than the first type wherein the ports are electrically coupled so that a first port is electrically coupled to a distinct second port to form a port pair;
means electrically coupled to the input for selecting a port pair to monitor; and
a display electrically coupled to the means for selecting and the input to display the port pair is being monitored;
wherein each port pair is assigned a unique number and the display is a light emitting digit display that displays the unique number of the port pair being monitored.
69. (Previously Presented) A monitor comprising:
an input for receiving signals from multiple ports wherein the ports include a plurality of first ports of a first type and a plurality of second ports of a second type that are different than the

first type wherein the ports are electrically coupled so that a first port is electrically coupled to a distinct second port to form a port pair;

means electrically coupled to the input for selecting a port pair to monitor; and

a display electrically coupled to the means for selecting and the input to display the port pair is being monitored;

wherein the means for selecting is a switch.

70. (Previously Presented) A monitor comprising:

an input for receiving signals from multiple ports wherein the ports include a plurality of first ports of a first type and a plurality of second ports of a second type that are different than the first type wherein the ports are electrically coupled so that a first port is electrically coupled to a distinct second port to form a port pair;

means electrically coupled to the input for selecting a port pair to monitor; and

a display electrically coupled to the means for selecting and the input to display the port pair is being monitored;

wherein the means for selecting is a pair of momentary switches.

71. (Previously Presented) A monitor comprising:

an input for receiving signals from multiple ports wherein the ports include a plurality of first ports of a first type and a plurality of second ports of a second type that are different than the first type wherein the ports are electrically coupled so that a first port is electrically coupled to a distinct second port to form a port pair;

means electrically coupled to the input for selecting a port pair to monitor; and

a display electrically coupled to the means for selecting and the input to display the port pair is being monitored;

wherein the display is a liquid crystal display.

72. (Previously Presented) A monitor circuit board assembly comprising:

an input for receiving signals from a plurality of port pairs of a converter;

a port pair selector for selecting which port pair to monitor;

a monitor circuit coupled to the input and port pair selector wherein the monitor circuit monitors at least one condition of the port pair selected; and

a display to indicate which of a plurality of port pairs is being monitored;
wherein the display is an LED digit display.

73. (Previously Presented) A monitor circuit board assembly comprising:
an input for receiving signals from a plurality of port pairs of a converter;
a port pair selector for selecting which port pair to monitor;
a monitor circuit coupled to the input and port pair selector wherein the monitor circuit monitors at least one condition of the port pair selected; and
a display to indicate which of a plurality of port pairs is being monitored;
wherein the display is a liquid crystal display.

74. (Previously Presented) A monitor circuit board assembly comprising:
an input for receiving signals from a plurality of port pairs of a converter;
a port pair selector for selecting which port pair to monitor;
a monitor circuit coupled to the input and port pair selector wherein the monitor circuit monitors at least one condition of the port pair selected; and
a display to indicate which of a plurality of port pairs is being monitored;
wherein the port pair selector is a switch.

75. (Previously Presented) A monitor circuit board assembly comprising:
an input for receiving signals from a plurality of port pairs of a converter;
a port pair selector for selecting which port pair to monitor;
a monitor circuit coupled to the input and port pair selector wherein the monitor circuit monitors at least one condition of the port pair selected; and
a display to indicate which of a plurality of port pairs is being monitored;
wherein the port pair selector is a pair of switches.

76. (Previously Presented) A monitor circuit board assembly comprising:
an input for receiving signals from a plurality of port pairs of a converter;

a port pair selector for selecting which port pair to monitor;
a monitor circuit coupled to the input and port pair selector wherein the monitor circuit monitors at least one condition of the port pair selected; and
a display to indicate which of a plurality of port pairs is being monitored;
wherein the pair of switches are momentary switches.

77. (Previously Presented) A monitor for a converter, the monitor comprising:
an input electrically coupled to a plurality of port pairs wherein each of the port pairs includes a port of a first type electrically coupled to a port of a second type wherein the first type accepts signals in a different format than the second type;
a selector coupled to the input for selecting one of the plurality of port pairs to monitor;
a monitor circuit for monitoring at least one condition of the port pair selected; and
a display coupled to the input for displaying the port pair being monitored and whether a fault condition is present at that port pair being monitored;
wherein the display is a liquid crystal display.

78. (Previously Presented) A monitor for a converter, the monitor comprising:
an input electrically coupled to a plurality of port pairs wherein each of the port pairs includes a port of a first type electrically coupled to a port of a second type wherein the first type accepts signals in a different format than the second type;
a selector coupled to the input for selecting one of the plurality of port pairs to monitor;
a monitor circuit for monitoring at least one condition of the port pair selected; and
a display coupled to the input for displaying the port pair being monitored and whether a fault condition is present at that port pair being monitored;
wherein the selector is a switch.

79. (Previously Presented) A monitor for a converter, the monitor comprising:
an input electrically coupled to a plurality of port pairs wherein each of the port pairs includes a port of a first type electrically coupled to a port of a second type wherein the first type accepts signals in a different format than the second type;
a selector coupled to the input for selecting one of the plurality of port pairs to monitor;
a monitor circuit for monitoring at least one condition of the port pair selected; and

a display coupled to the input for displaying the port pair being monitored and whether a fault condition is present at that port pair being monitored;
wherein the selector includes a pair of switches.

80. (Previously Presented) A monitor for a converter, the monitor comprising:
an input electrically coupled to a plurality of port pairs wherein each of the port pairs includes a port of a first type electrically coupled to a port of a second type wherein the first type accepts signals in a different format than the second type;
a selector coupled to the input for selecting one of the plurality of port pairs to monitor;
a monitor circuit for monitoring at least one condition of the port pair selected; and
a display coupled to the input for displaying the port pair being monitored and whether a fault condition is present at that port pair being monitored;
wherein the pair of switches are momentary switches.